

21st International Magnetic Measurement workshop

Grenoble, 24-28 June 2019

Measurement and fiducialization of the ESRF-EBS magnets

Gaël Le Bec, Loïc Lefebvre, Christophe Penel, Joël Chavanne



The European Synchrotron

I. Introduction

- Magnets for the EBS

II. Measurement and fiducialization of the magnet series

- Initial plans, tolerances, difficulties encountered
- Measurements and fiducialization at the ESRF
- Main results

III. Magnet calibration and measurement of combined function magnets

- Calibration, cycling and thermal effects
- Curved dipole-quadrupoles
- Combined function sextupole-correctors

IV. Conclusion

I. Introduction

- Magnets for the EBS

II. Measurement and fiducialization of the magnet series

- Initial plans, tolerances, difficulties encountered
- Measurements and fiducialization at the ESRF
- Main results


III. Magnet calibration and measurement of combined function magnets

- Calibration, cycling and thermal effects
- Curved dipole-quadrupoles
- Combined function sextupole-correctors

IV. Conclusion

Magnets for the EBS

- About 1000 magnets
- Small aperture magnets
- PM dipoles (see Joël's talk)
- Quadrupoles with gradient ~ 90 T/m
- Dipole-quadrupoles
- Sextupoles
- Octupoles



I. Introduction

- Magnets for the EBS

II. Measurement and fiducialization of the magnet series

- Initial plans, tolerances, difficulties encountered
- Measurements and fiducialization at the ESRF
- Main results



III. Magnet calibration and measurement of combined function magnets

- Calibration, cycling and thermal effects
- Curved dipole-quadrupoles
- Combined function sextupole-correctors

IV. Conclusion

Alignment tolerances

- Fiducialization errors within $\pm 50 \mu\text{m}$
- Magnet centre positioned within $\pm 50 \mu\text{m}$ by mechanical shims (depends on magnet families)
- Roll angle tolerance within $\pm 50 \mu\text{rad}$ initially, relaxed to $\pm 130 \mu\text{rad}$



Field quality

- The ESRF was responsible for the magnetic design
- Magnets with shape and assembly errors were simulated

Simulated standard deviation of multipoles for the high gradient quads, at 7 mm radius, for a ± 0.04 mm tolerance


n	σ_n	$3\sigma_n$	
1	16.3	49.0	Fiducialization
2	10.0	30.0	Current
3	4.8	14.4	←
4	1.9	5.7	Magnetic design
5	1.0	3.1	←
6	0.5	1.7	Magnetic design
7	0.3	0.9	
8	0.2	0.5	Magnetic design
9	0.1	0.3	
10	0.06	0.2	Magnetic design

Large values of a_3, b_3, a_5 or b_3 indicate a quality issue and trigs further investigations

- Mechanical tolerances
- Material
- Coil windings

Initial plans

- Measurements and fiducialization to be done by the magnet suppliers
- Five ESRF stretched wire measurement benches installed at supplier premises
- One (far from Grenoble) supplier encouraged to use its own bench
- Shims to be installed by suppliers for positioning the magnet centres
- Site Acceptance Tests at the ESRF on randomly selected magnets



**Design view of a stretched wire bench
installed at magnet factory**

Difficulties encountered

- Our benches are prototypes rather than commercial products
 - Maintenance and software updates needs “expert” users
 - Press-button measurement macros developed... with a few bugs

Difficulties encountered

- Our benches are prototypes rather than commercial products
 - Maintenance and software updates needs “expert” users
 - Press-button measurement macros developed... with a few bugs
- Calibration of the benches
 - Weekly measurement of a reference magnet

Difficulties encountered

- Our benches are prototypes rather than commercial products
 - Maintenance and software updates needs “expert” users
 - Press-button measurement macros developed... with a few bugs
- Calibration of the benches
 - Weekly measurement of a reference magnet

Fiducialisation

→ The

→ Meas

magnet

→ Meas

usual to

→ The

were ou

The fiducialization was the main difficulty

Solutions envisaged

1. To send laser trackers and staff to the factories
2. **To fiducialize all magnets in house (adopted)**

one with

pliers

Measurement zone at the ESRF


- 132 PM dipoles assembled and measured
 - Two stretched wire measurement benches
- About 800 magnets to characterize in ~ 1 year
 - Two additional benches dedicated to the SAT and fiducialization



Measurement zone at the ESRF

- 132 PM dipoles assembled and measured
 - Two stretched wire measurement benches
- About 800 magnets to characterize in ~ 1 year
 - Two additional benches dedicated to the SAT and fiducialization

PM dipole
assembly and
measurements




Pre-series tests and
fiducialization zone

Measurement zone at the ESRF

- 132 PM dipoles assembled and measured
 - Two stretched wire measurement benches
- About 800 magnets to characterize in ~ 1 year
 - Two additional benches dedicated to the SAT and fiducialization


Magnet handling and
short term storage



Fiducialization and
measurements

MEASUREMENT AND FIDUCIALIZATION OF THE MAGNET SERIES


Coordinate measurements with two laser tracker stations



[Courtesy D. Martin, ESRF, IWAA2018]

MEASUREMENT AND FIDUCIALIZATION OF THE MAGNET SERIES


Coordinate measurements with two laser tracker stations



[Courtesy D. Martin, ESRF, IWAA2018]

MEASUREMENT AND FIDUCIALIZATION OF THE MAGNET SERIES


Coordinate measurements with two laser tracker stations



[Courtesy D. Martin, ESRF, IWAA2018]



MEASUREMENT AND FIDUCIALIZATION OF THE MAGNET SERIES

Coordinate measurements with two laser tracker stations



[Courtesy D. Martin, ESRF, IWAA2018]


Uncertainty analysis



Uncertainty analysis

1. Calibration of the wire support references

$$U_x = 15 \mu\text{m}, U_z = 18 \mu\text{m}$$




Uncertainty analysis

1. Calibration of the wire support references

$$U_X = 15 \mu\text{m}, U_Z = 18 \mu\text{m}$$

2. Magnetic measurement

$$U_{MM} = 4 \mu\text{m} \text{ (including wire diameter)}$$




Uncertainty analysis: one reference

3. Measurements of the wire supports

$$\varepsilon = \frac{\varepsilon_1 + \varepsilon_2}{2} + \frac{\varepsilon_2 - \varepsilon_1}{L} y_0$$


$$U_{WS}^2 = \text{Var}\left(\frac{\varepsilon_1 + \varepsilon_2}{2}\right) + \text{Var}\left(\frac{\varepsilon_2 - \varepsilon_1}{L} x_0\right) + \text{Cov}\left(\frac{\varepsilon_1 + \varepsilon_2}{2}, \frac{\varepsilon_2 - \varepsilon_1}{L} y_0\right)$$

$$= \frac{\sigma_{WS}^2}{2L^2} (L^2 + 4y_0^2)$$



Uncertainty analysis: four references

3. Measurements of the wire supports $U_{WS}^2 = \frac{\sigma_{WS}^2}{4L^2} (L^2 + 4\Delta y^2)$



Uncertainty analysis

4. Measurement of the magnet reference $U_{REF}^2 = \sigma_{REF}^2$

MEASUREMENT AND FIDUCIALIZATION OF THE MAGNET SERIES

Uncertainty analysis

Calibration of the wire supports Magnetic measurements Measurements of the wire support references Measurements of the magnet references


$$U^2 = U_{X,Z}^2 + U_{MM}^2 + U_{WS}^2 + U_{REF}^2$$
$$= U_{X,Z}^2 + U_{MM}^2 + \frac{\sigma_{WS}^2}{4L^2} (L^2 + 4\Delta y^2) + \sigma_{REF}^2$$

Fiducialization uncertainties

$$U_{Horiz} = 20 \mu\text{m}, U_{Vert} = 22 \mu\text{m}$$

with $U_X = 15 \mu\text{m}$, $U_Z = 18 \mu\text{m}$, $U_{MM} = 4 \mu\text{m}$, $\sigma_{WS} = 14 \mu\text{m}$, $\sigma_{REF} = 10 \mu\text{m}$,
 $L = 1.2 \text{ m}$ and $\Delta y = 1 \text{ cm}$

Uncertainty analysis – How much can fiducialization be improved?

$$U^2 = U_{X,Z}^2 + U_{MM}^2 + U_{WS}^2 + U_{REF}^2$$


- Using a more accurate CMM may allow to decrease these numbers
- Measure the wire supports instead of its references

With a laser tracker

$$U_{X,Z} = 10 \mu\text{m}, U_{MM} = 4 \mu\text{m}, \sigma_{WS} = 10 \mu\text{m}, \sigma_{REF} = 10 \mu\text{m},$$
$$L = 1.2 \text{ m and } \Delta x = 1 \text{ cm} \rightarrow U = 15.5 \mu\text{m}$$

With a CMM



$$U_{X,Z} = 0 \mu\text{m}, U_{MM} = 4 \mu\text{m}, \sigma_{WS} = 5 \mu\text{m}, \sigma_{REF} = 5 \mu\text{m},$$
$$L = 1.2 \text{ m and } \Delta x = 1 \text{ cm} \rightarrow U = 7.5 \mu\text{m}$$

This would imply a lot of engineering...

... and would not solve all possible issues!

MEASUREMENT AND FIDUCIALIZATION OF THE MAGNET SERIES

Uncertainty analysis – How much can fiducialization be improved?



Uncertainty analysis – How much can fiducialization be improved?

- Using a more accurate CMM
- Measure the wire supports instead of its references
- Use finer wire
- Frequent measurements of a reference magnets are necessary (recalibration once per week during the EBS magnet measurements)

Fiducialization uncertainties are NOT alignment uncertainties

- Magnet alignment on girders
 - Position shims may help as it avoid a 2nd measurement of the references
- Alignment between girders
- Transportation(s)
- Thermal effects (time constants ~ 5 h)
- ...




MEASUREMENT AND FIDUCIALIZATION OF THE MAGNET SERIES

References before fiducialization vs magnetic center




- Loose tolerances specified (the position errors were measured)
- Show how the references are improved by the fiducialization
- Depends on the design

Magnet family	Horiz. σ_X [mm]	Vert. σ_Z [mm]	Long. σ_Y [mm]
Q-MG	0.14	0.14	0.26
Q-HG	0.28	0.18	0.38
S	0.11	0.14	0.22
DQ	0.12	0.14	0.22

One order of magnitude improvement by fiducialization



Alignment shims



Vertical position and roll angle of shimmed QD2 quadrupoles
(tolerance: $\pm 50 \mu\text{m}$, $\pm 130 \mu\text{rad}$)

Vertical position: $-3 \pm 24 \mu\text{m}$, roll angle: $-19 \pm 60 \mu\text{rad}$

Vertical position: $-3 \pm 33 \mu\text{m}$ if the bench uncertainty is $\pm 22 \mu\text{m}$

QD2 moderate grad. quads

220 magnets

Gradient $\sim 50 \text{ T/m}$

Bore radius: 16.4 mm

GFR radius: 13 mm

Iron length: 212 mm


Laminated FeSi, machined poles

Chamfers at pole extremities

Alignment shims

MEASUREMENT AND FIDUCIALIZATION OF THE MAGNET SERIES

Higher order multipoles



QD2 moderate grad. quads

220 magnets

Gradient ~ 50 T/m



Bore radius: 16.4 mm

GFR radius: 13 mm

Iron length: 212 mm


Laminated FeSi, machined poles

Chamfers at pole extremities



Significantly higher st. dev. for b_4 and b_6
Accuracy of the extremity chamfer machining?

Higher order multipoles



QF8 high grad. quads

66 magnets

Gradient: 88 T/m



Bore radius: 12.5 mm

GFR radius: 7 mm

Iron length: 484 mm


Solid iron (AISI 1010) poles, wire cut

No chamfer at extremity



Dashed lines: mechanical errors with 23 μm st. dev., corresponding to a $\pm 40 \mu\text{m}$ uniform distribution of errors

Higher order multipoles



SD1 sextupoles

128 magnets


Gradient: 1700 T/m²

Bore radius: 19.2 mm


GFR radius: 13 mm

Iron length: 166 mm

Solid iron (AISI 1010) poles
wire cut



Vertical position: $-10 \pm 34 \mu\text{m}$
if the bench uncertainty is $\pm 22 \mu\text{m}$



Simulations: mechanical errors
with 23 μm st. dev.,
corresponding to a $\pm 40 \mu\text{m}$
uniform distribution of errors

I. Introduction

- Magnets for the EBS

II. Measurement and fiducialization of the magnet series

- Initial plans, tolerances, difficulties encountered
- Measurements and fiducialization at the ESRF
- Main results

III. Magnet calibration and measurement of combined function magnets

- Calibration, cycling and thermal effects
- Curved dipole-quadrupoles
- Combined function sextupole-correctors


IV. Conclusion

Thermal effects

Moderate gradient quads

Thermal time constant: 5.6 h

$$\Delta G/G = 4 \times 10^{-4}$$



Thermal effects


Moderate gradient quads

Thermal time constant: 5.6 hours

$$\Delta G/G = 4 \times 10^{-4}$$

Current cycling

- Various cycling schemes studied
- Cycling at restarts, but not during operations: accuracy of current settings?
 - Depends on ΔI
 - Limits the current range



Thermal effects

Moderate gradient quads

Thermal time constant: 5.6 hours


$$\Delta G/G = 4 \times 10^{-4}$$

Current cycling

- Various cycling schemes studied
- Cycling at restarts, but not during operations: accuracy of current settings?
 - Depends on ΔI
 - Limits the current range

Excitation curves

- Being remeasured using cycle C2 and 5 hours warming time



$\Delta G/G$ for different cycling parameters

	$\Delta I = 2 A$	$\Delta I = 6 A$
C1	2.4×10^{-4}	
C2	0.5×10^{-4}	
C3	0.5×10^{-4}	3.4×10^{-4}

Dipole-quadrupoles (DQs)

Main parameters (DQ1)

Integrated field: 584 Tmm

Integrated gradient: 38.4 T

Iron length: 1028 mm


Pole radius of curvature: 35.21 m

GFR: 14 x 10 mm x mm

Machined solid iron plates

Curved poles

64 DQ1 and 32 DQ2 installed



Design view of the DQ1 magnet


DQ measurement method

Hall probe mapping

- Done on pre-series magnets
- Time consuming
- Limited accuracy: homogeneity and multipoles are difficult to extract

Stretched wire measurements


- Preliminary method presented at the previous IMMW
- Some improvements done



Design view of the DQ1 magnet

DQ measurement method

$$B \approx \sum_{n=1}^N (\beta_n + i\alpha_n) \left(\frac{u}{\rho_0} \right)^{n-1}$$



$$I = \int B dy = \sum_{n=1}^{\infty} (b_n + ia_n) \left(\frac{x' + iz}{\rho_0} \right)^{n-1}$$

$$\approx \sum_{n=1}^N \frac{\beta_n + i\alpha_n}{\rho_0^{n-1}} \frac{1}{L} \int_{-\frac{L}{2}}^{\frac{L}{2}} \left(x' + \frac{l^2}{2R} + iz \right)^{n-1} dl$$

$$\begin{pmatrix} b_1 + ia_1 \\ \vdots \\ b_N + ia_N \end{pmatrix} = \begin{pmatrix} A_{11} & \dots & A_{1N} \\ \vdots & \ddots & \vdots \\ 0 & \dots & A_{NN} \end{pmatrix} \begin{pmatrix} \beta_1 + i\alpha_1 \\ \vdots \\ \beta_N + i\alpha_N \end{pmatrix} \rightarrow \begin{pmatrix} \beta_1 + i\alpha_1 \\ \vdots \\ \beta_N + i\alpha_N \end{pmatrix}$$

DQ measurement method

Magnet alignment sequence

Field integrals and 2nd field integrals on straight lines

- Magnet centre (including longitudinal position)
- Yaw and pitch angles
- Magnetic length
- Radius of curvature of the poles

Integrated field multipoles

Measured on a straight line

- Conversion to “pseudo multipoles” integrated along a parabola

(Paper submitted to PRAB)

DQ measurement method

Simulation results

3D model implemented with the Radia code

Normal pseudo multipole coefficients at 7 mm,
computed with different methods

	Trajectory	Parabola	Straight to parabola
1	10000	10000	10000
2	-4550.8	-4548.0	-4548.5
3	2.5	2.1	4.1
4	3.7	3.8	3.7
5	-2.7	-2.6	-2.9
6	-9.0	-9.3	-9.6
7	2.9	2.8	1.9
8	9.5	10.1	11.0

Can be obtained from SW measurements

COMBINED DIPOLE-QUADRUPOLE MEASUREMENTS

DQ stretched wire measurement results

Gradient mag. length: 1047 ± 1.4 mm (sim: 1044 mm)


Pole radius of curvature: 32.12 ± 0.8 m (sim: 32.21 m)

Alignment

Repeatability of the mag. measurement: $4 \mu\text{m}$
(without removing the wire)

Multipoles


	b_1	β_1	a_1	α_1
1	10000	10000	7.0 ± 0.7	6.4 ± 0.7
2	5020.8 ± 1.0	4590.9 ± 0.9	0.4 ± 0.3	-0.1 ± 0.3
3	-3.0 ± 0.2	-5.0 ± 0.2	1.3 ± 0.2	1.8 ± 0.2
4	-4.1 ± 0.3	-5.6 ± 0.4	-1.1 ± 0.1	-1.3 ± 0.2
5	-0.7 ± 0.3	5.0 ± 0.2	0.4 ± 0.2	0.4 ± 0.2
6	4.7 ± 0.1	19.1 ± 0.4	-0.1 ± 0.1	0.4 ± 0.1
7	13.95 ± 0.3	8.3 ± 0.5	-0.5 ± 0.1	-0.6 ± 0.1
8	-3.1 ± 0.1	-9.1 ± 0.2	0.2 ± 0.1	0.3 ± 0.2



Gradient homogeneity
computed from stretched wire
measurements
Specification: $\pm 1\%$ within the
14x10 mm ellipse

Sextupole correctors

- 1 main PS, 6 main coils
→ b_3
- 4 corrector PS, 6 correction coils
→ a_1, b_1, a_2, b_3
- Correctors and skew quad settings must not affect the sextupole, and *vice versa*
- $b_3(I_{Main}, I_1 \dots I_4)$ is non-linear
- and $a_1, b_1, a_2(I_{Main}, I_1 \dots I_4)$ are not linear in $I_1 \dots I_4$!



Sextupole correctors

- A 5 inputs and 4 outputs NL numerical model was developed
- Linear and quadratic terms in $I_1 \dots I_4$
- Cubic spline interpolation in I_{MAIN}

Forward computations

$$I_{MAIN}, I_1 \dots I_4 \rightarrow a_1 \dots b_3$$

Inverse computations


$$a_1 \dots b_3 \rightarrow I_{MAIN}, I_1 \dots I_4$$

Difficulties

A lot of parameters
(81 parameters at
symmetry taken in

In simulations, the errors between a 3D model
(Radia) and the NL model are $\sim 10^{-4}$

must be used



Numerical sextupole model

Sextupole correctors

- All coefficients can be obtained from measurements at 8 corrector currents

$$\begin{pmatrix} 0 \\ 0 \\ 0 \\ 0 \end{pmatrix}$$

Sextupole at I_{MAIN}

$$\begin{pmatrix} 1 \\ 0 \\ 0 \\ 0 \end{pmatrix} \begin{pmatrix} -1 \\ 0 \\ 0 \\ 0 \end{pmatrix}$$

Linear and quadratic terms PS 1 and PS 3

$$\begin{pmatrix} 0 \\ 1 \\ 0 \\ 0 \end{pmatrix} \begin{pmatrix} 0 \\ -1 \\ 0 \\ 0 \end{pmatrix}$$

Linear and quadratic terms PS 2 and PS 4

$$\begin{pmatrix} 0 \\ 1 \\ 1 \\ 0 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \\ -1 \\ 0 \end{pmatrix} \begin{pmatrix} 0 \\ 1 \\ 0 \\ -1 \end{pmatrix}$$

Crossed terms

- Each single multipole measurement (SW, rotating coil) give $a_1 \dots b_3$

8 corrector current settings at each main current
 → Measurement feasible in a reasonable time

COMBINED SEXTUPOLE-CORRECTORS

Sextupole correctors

- Cycling and “degaussing” sequence defined
- Symmetries used to clean the data
- 15 current settings at each main current

Raw multipoles measured at a given I_{MAIN}

I_{MAIN} (A)	I_1 (A)	I_2 (A)	I_3 (A)	I_4 (A)	a_1 (T mm)	b_1 (T mm)	a_2/r_0 (T)	b_3/r_0^2 (T / mm)
90	0	0	0	0	0.081586	-0.25307	-0.02438	0.457691
90	-2	0	0	0	4.080059	-2.5587	-0.02304	0.449297
90	0	0	-2	0	-3.94271	-2.58475	-0.02333	0.44921
90	2	0	0	0	-3.24079	1.659555	-0.02389	0.464308
90	0	0	2	0	3.406766	1.64995	-0.02331	0.464314
90	0	-2	0	0	0.095563	-2.15319	0.055295	0.461032
90	0	0	0	2	0.075286	-2.18184	-0.10247	0.461091
90	0	2	0	0	0.065564	1.976168	-0.11822	0.453468
90	0	0	0	-2	0.083707	2.010712	0.074977	0.453385
90	-2	-2	0	0	4.021977	-4.52737	0.06373	0.452847
90	0	0	-2	2	-3.87582	-4.57373	-0.10912	0.452872
90	-2	0	-2	0	0.065562	-5.27636	-0.02135	0.439055
90	2	0	2	0	0.083672	3.567156	-0.02289	0.470726
90	0	-2	0	2	0.085843	-4.12948	-0.02378	0.464452
90	0	2	0	-2	0.068178	4.422182	-0.02006	0.449141

Sextupole correctors

- Cycling and “degaussing” sequence defined
- Symmetries used to clean the data
- 15 current settings at each main current

Processed multipoles at a given I_{MAIN} (model parameters)

I_{MAIN} (A)	I_1 (A)	I_2 (A)	I_3 (A)	I_4 (A)	a_1 (T mm)	b_1 (T mm)	a_2/r_0 (T)	b_3/r_0^2 (T / mm)
90	0	0	0	0	0	0	0	0.457691
90	-2	0	0	0	4.011387	-2.31865	0	0.449297
90	2	0	0	0	-3.32378	1.907827	0	0.464308
90	0	-2	0	0	0	-1.91444	0.078882	0.461032
90	0	2	0	0	0	2.246515	-0.0966	0.453468
90	-2	-2	0	0	3.948899	-4.29747	0.086426	0.452847
90	-2	0	-2	0	0	-5.02329	0	0.439055
90	0	-2	0	2	0	-4.27583	0	0.464452

COMBINED SEXTUPOLE-CORRECTORS

Sextupole correctors

- Cycling and “degaussing” sequence defined
- Symmetries used to clean the data
- 15 current settings at each main current

Processed multipoles at a given I_{MAIN} (model parameters)

I_{MAIN} (A)	I_1 (A)	I_2 (A)	I_3 (A)	I_4 (A)	a_1 (T mm)	b_1 (T mm)	a_2/r_0 (T)	b_3/r_0^2 (T / mm)
90	0	0	0	0	0	0	0	0.457691
90	-2	0	0	0	4.011387	-2.31865	0	0.449297
90	2	0	0	0	-3.32378	1.907827	0	0.464308
90	0	-2	0	0	0	-1.91444	0.078882	0.461032
90	0	2	0	0	0	2.246515	-0.0966	0.453468
90	-2	-2	0	0	3.948899	-4.29747	0.086426	0.452847
90	-2	0	-2	0	0	-5.02329	0	0.439055
90	0	-2	0	2	0	-4.27583	0	0.464452

Sextupole correctors

Random multipole strength specifications



Currents



Measured multipole strengths specifications

Sample test results at 90 A (i.e. saturated)

		Test #1		Test #2	
		Spec.	Meas	Spec.	Meas
a_1	(T mm)	0	0.034	0	0.003
b_1	(T mm)	6	5.96	0	0.097
a_2/r_0	(T)	0	-0.003	0.13	0.1287
b_3/r_0^2	(T/mm)	0.46984	0.46916	0.46984	0.46956

Work in progress...

I. Introduction

- Magnets for the EBS

II. Measurement and fiducialization of the magnet series

- Initial plans, tolerances, difficulties encountered
- Measurements and fiducialization at the ESRF
- Main results

III. Magnet calibration and measurement of combined function magnets

- Calibration, cycling and thermal effects
- Curved dipole-quadrupoles
- Combined function sextupole-correctors

IV. Conclusion

Measurement of magnet series

- Late decision to characterize all magnets in house
- About 800 electromagnets measured and fiducialized in about 1 year
- Stretched-wire benches used successfully for calibration, field mapping and fiducialization

Fiducialization

- Two laser tracker stations for each magnet
- Benches recalibrated every week vs a reference magnet
- Fiducialization uncertainties estimated to $U_X = 20 \mu\text{m}$ and $U_Z = 23 \mu\text{m}$
(These are not magnet to magnet alignment uncertainties!)

Higher order multipoles

- Depends on the technology (laminated, solid iron, machined, wired cut, chamfer)

Calibration

- Thermal effects stronger than cycling effects
- Cycling scheme defined

Curved dipole-quadrupoles

- Stretched wire measurement sequence developed and demonstrated
- Alignment, pole radius of curvature and pseudo multipole measured with SW

Combined Sextupole-correctors

- NL model developed
- Tests in progress

ACKNOWLEDGMENTS

ESRF labs and groups

Insertion Devices and Magnets

Survey and Alignment

Mechanical Engineering

Logistics and handling

Magnet manufacturers

Tesla, Danfysik, Budker Institute of Nuclear Physics

MANY THANKS FOR YOUR ATTENTION

